

SOLSTICE® N41 (R-466A)

Technical Information

Solstice N41 (R-466A*) is a nonflammable, reduced global-warming-potential (GWP) refrigerant, designed to replace R-410A in stationary residential and commercial air conditioning systems. Solstice N41 offers an excellent capacity and efficiency match for R-410A. Solstice N41 is the only R-410A replacement that offers the combination of nonflammability with a GWP 60% lower than R-410A.



APPLICATIONS

- Residential A/C systems
- Commercial A/C systems, such as chiller equipment

ENVIRONMENTAL & SAFETY BENEFITS

- Nonflammable (ASHRAE A1) (preliminary)
- Reduced GWP of 733 (60% lower than R-410A)
- Non-ozone-depleting

OPERATIONAL BENEFITS

- Energy efficiency equal to or better than R-410A
- Close performance match to R-410A
- No change in codes or service practices needed
- Compatible with existing R-410A equipment design

Solstice N41 Properties

ASHRAE Number (provisional)	466A
Composition	R-32 / R-125 / R-131I
Weight %	49%/11.5%/39.5%
Molecular Weight (g/mol)	80.7
Boiling Point at 1 atm	-51.7 °C
Critical Pressure	5908 kpa
Critical Temperature	83.8 °C
Liquid Density at 2.0 °C	1259 kg/m3
Ozone Depletion Potential (CFC-11 = 1.0)	~0
Global Warming Potential	733
ASHRAE Safety Classification	A1 (preliminary)
Full Temperature Glide at 20° C (if applicable)	1.5 °K
WEEL (8-hr TWA)	860



Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Honeywell Refrigerants

115 Tabor Road
Morris Plains, NJ 07950
800-631-8138
www.honeywell-refrigerants.com

4171 FP | September 2019
©2019 Honeywell International Inc. All rights reserved.

Honeywell