



**REFRIGERANTS  
WITH  
THE FUTURE  
IN MIND**

**Honeywell**

# HONEYWELL REFRIGERANTS APPLICATION GUIDE

## COMMERCIAL REFRIGERATION

ASHRAE #	GWP <sup>1</sup>	Trade Name	Replaces	Blend Composition / ASHRAE Classification <sup>2</sup>	Typical Lubricant <sup>3</sup>	Comments
	AR5		ASHRAE #			
R-1234yf	1	Solstice yf	R-134a	HFO (single component fluid) ASHRAE A2L	Alkylbenzene, Synthetic (POE, PAG)	Ultra-low GWP and higher capacity solution for vending machines, plug in cabinets, and water chillers. <b>New equipment only</b>
R-1234ze	1	Solstice ze	R-134a	HFO (single component fluid) ASHRAE A2L	Alkylbenzene, Synthetic (POE, PVE, PAG)	Ultra-low GWP and high efficiency solution for vending machines, plug in cabinets, low side of cascade systems and water chillers. <b>New equipment only</b>
R-455A	146	Solstice L40X	R-404A R-507	R-32/R-1234yf/CO <sub>2</sub> ASHRAE A2L	Synthetic (POE)	Low GWP blend for low, medium, and high temperature systems, low side of cascade systems. Excellent option for self-contained units. Close performance match to R-404A. <b>New equipment only</b>
R-450A	547	Solstice N13	R-134a R-401A R-401B R-409A	R-134a/R-1234ze ASHRAE A1	Synthetic (POE)	GWP is 58% lower than R-134a >90% capacity with similar efficiency (101-103% vs R-134a). New equipment and retrofits
R-513A	573	Solstice 513A	R-134a	HFO R-1234yf/ R-134a	Synthetic (POE)	Close performance match to R-134a for retrofit and new systems
R-515B	299	Solstice N15	R-134a	R-1234ze/R-227ea	Synthetic (POE)	Reduced GWP replacement for 134a in new systems, low side of cascade systems. GWP 77% lower than R134a.
R-448A	1273	Solstice® N40	R-404A R-402A R-408A R-22 R-507 R-502	R-32/R-125/ R-134a/R-1234ze/R-1234yf ASHRAE A1	Synthetic (POE)	Global warming potential (GWP) is 68% lower than R-404A. 5% - 16% lower energy consumption vs R-404A. Best capacity and efficiency alternative to R-22 and R-404A. New equipment and retrofits.
R-134a	1300	Genetron® 134a	R-12	R-134a ASHRAE A1	Synthetic (POE, PVE)	Similar energy efficiency and good capacity match compared to R-12. Performs well in small hermetic systems
R-407F	1674	Genetron Performax® LT	R-22 R-404A R-402A R-408A R-507	R-32/R-125/ R-134a ASHRAE A1	Synthetic (POE, PVE)	Good capacity match to R-22. Lower discharge temperature vs R-22. Cost-effective alternative New equipment and retrofits.
R-452A	1945	Solstice 452A	R-404A R-507	R-1234yf/ R-32/R-125 ASHRAE A1	Synthetic (POE)	Low and medium temperature alternative for R-404A. Discharge temperature similar to R-404A. Transport, condensing units, self-contained units. New equipment and retrofits.
Service Gas Refrigerants						
R-404A	3943	Genetron 404A		R-125/R-143a/ R-134a ASHRAE A1	Synthetic (POE, PVE)	R-404A and R-507 are HFC blends with high GWP. These refrigerants are subject to future regulations on usage. Honeywell recommends utilizing HFO blends such as Solstice N40 for new equipment and as a replacement for R-404A and R-507 in existing equipment
R-507	3985	Genetron AZ-50®		R-125/R-143a ASHRAE A1	Synthetic (POE, PVE)	
R-22	1760			R-22 ASHRAE A1	Mineral oil	No new R-22 refrigerant can be manufactured or imported into the U.S. or Canada. Any servicing must use stockpiled or reclaimed material.

## COMMERCIAL AIR CONDITIONING / CHILLERS

ASHRAE#	GWP <sup>1</sup>	Trade Name	Replaces	Blend Composition / ASHRAE Classification <sup>2</sup>	Typical Lubricant <sup>3</sup>	Comments
	AR5		ASHRAE #			
R-1234ze	1	Solstice ze	R-134a	HFO (Single component fluid) ASHRAE A2L	Alkylbenzene Synthetic (POE, PVE, PAG)	Ultra-low GWP solution, best performance match to R-134a. <b>New equipment</b> (chillers, small systems)
R-1233zd	1	Solstice zd	R-123	HFO (Single component fluid) ASHRAE A1	Alkylbenzene Mineral oil Synthetic (POE, PVE)	Ultra-low GWP solution for low pressure chillers. <b>New equipment only</b> Organic Rankine Cycle
R-450A	547	Solstice N13	R-134a, R-409A, R-401A, R-401B	R-134a/R-1234ze ASHRAE A1	Synthetic (POE)	GWP is 58% lower than R-134a >90% capacity with similar efficiency (101-103% vs R-134a). New equipment and retrofits
R-513A	573	Solstice 513A	R-134a	HFO R-1234yf/ R-134a	Synthetic (POE)	Close performance match to R-134a for retrofit and new systems
R-515B	299	Solstice N15	R-134a / R-124	R-1234ze/R-227ea	Synthetic (POE)	For use in chillers and for cooling systems for high ambient conditions. GWP 77% lower than R134a. 23% capacity gain over R-124 and similar efficiency in high ambient applications.
R-466A	733	Solstice N41	R-410A	R-32 / R-125 / R-1311 ASHRAE A1 (preliminary)	Synthetic (POE)	Nonflammable GWP is 60% lower than R-410A <b>New Equipment Only</b>
R-245fa	858	Genetron 245fa	R-11 R-123	HFC (Single component fluid) ASHRAE B1	Synthetic (POE, PVE)	Equipment redesign, Organic Rankine Cycle heat transfer fluid. <b>New equipment only</b>
R-134a	1300	Genetron 134a	R-12 R-500	HFC (Single component fluid) ASHRAE A1	Synthetic (POE, PVE)	Similar energy efficiency and good capacity match to R-12. New equipment and retrofits
R-407C	1624	Genetron 407C	R-22 R-500	R-32/R-125/R-134a ASHRAE A1	Synthetic (POE)	Best retrofit alternative to R-22. Close performance match with slightly higher operating pressures. New equipment and retrofits
R-410A	1923	Genetron AZ-20®	R-22	R-32/R-125 ASHRAE A1	Synthetic (POE)	High pressure, high efficiency <b>New equipment only</b>
<b>Service gas</b>						
R-123	79	Genetron 123	R-11 (HCFC)	HFC (Single component fluid) ASHRAE B1	Alkylbenzene Mineral oil Synthetic (POE, PVE)	Phased out 2020



## RESIDENTIAL/LIGHT COMMERCIAL AIR CONDITIONING/HEAT PUMP

ASHRAE #	GWP <sup>1</sup>	Trade Name	Replaces	Blend Composition / ASHRAE Classification <sup>2</sup>	Typical Lubricant <sup>3</sup>	Comments
	AR5		ASHRAE #			
R-466A	733	Solstice N41	R-410A	R-32 / R-125 / R-1311 ASHRAE A1 (preliminary)	Synthetic (POE)	Nonflammable. GWP is 60% lower than R-410A. <b>New Equipment Only</b>
R-134a	1300	Genetron 134a	R-12	HFC (Single component fluid)	Synthetic (POE)	Similar energy efficiency and good capacity match compared to R-12 New equipment and retrofits
			R-500	ASHRAE A1	Alkylbenzene	
R-407C	1624	Genetron 407C	R-22	R-32/R-125/R-134a	Synthetic (POE)	Best retrofit alternative to R-22. Close performance match with slightly higher operating pressures New equipment and retrofits
			R-500	ASHRAE A1		
R-410A	1923	Genetron AZ-20	R-22	R-32/R-125 ASHRAE A1	Synthetic (POE)	High pressure, high efficiency <b>New equipment only</b>
R-422D	2477	Genetron 422D	R-22	R-125/R-134a/R-600a ASHRAE A1	Mineral Oil Synthetic (POE)	Use of synthetic (POE) will enhance oil return, if required. Retrofits.

## MOBILE AIR CONDITIONING / AUTOMOTIVE

ASHRAE #	GWP <sup>1</sup>	Trade Name	Replaces	Blend Composition/ ASHRAE Classification <sup>2</sup>	Typical Lubricant <sup>3</sup>	Comments
	AR5		ASHRAE #			
R-1234yf	1	Solstice yf	R-134a	HFO (Single component fluid) ASHRAE A2L	Synthetic (POE, PAG)	Ultra-low GWP solution <b>New equipment only</b> (small systems)
R-134a	1300	Genetron 134a	R-12	HFC (Single component fluid) ASHRAE A1	Synthetic (POE, PVE)	Similar energy efficiency and good capacity match to R-12

<sup>1</sup>Listing of GWP Values as per Report IPCC WG1 AR5 (100-yr time horizon)

(a) CFC=Chlorofluorocarbon; HCFC=Hydrochlorofluorocarbon; HFC=Hydrofluorocarbon; H=Hydrocarbon; FC=Fluorocarbon; HFO = Hydrofluoro-olefin

<sup>2</sup>**ASHRAE Classification Guide:**

ASHRAE A1: Nonflammable, low toxicity

ASHRAE A2L: Mildly flammable, low toxicity

ASHRAE B1: low flammability, higher toxicity

<sup>3</sup>Check with the compressor manufacturer for their recommended lubricant

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

**For more information visit**

[www.honeywell-refrigerants.com](http://www.honeywell-refrigerants.com)

**Honeywell Refrigerants**

115 Tabor Road

Morris Plains, NJ 07950

800-631-8138



8826 FP | August 2020  
©2020 Honeywell International Inc.

**THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT**

**Honeywell**